

CONTAINERISED SELF BUNDED TANK RANGE



**SUITABLE FOR THE STORAGE AND DISPENSING OF
DIESEL, LUBRICANTS, KEROSENE AND PETROL.**

FEATURES

- Integrated Bunded Pump Bay and Tank Access Platform design providing access to the full tank functionality in one convenient location on the tank.
- Unique rounded rectangular tank profile maximises the storage capacity of the tank and provides the strength of a cylindrical design.
- Rounded roof profile that will not pool water / snow or sand.
- CSC plated as 10ft / 20ft / 40ft / 48ft Standard Container.
- Dispensing Equipment housed within a lockable bunded pump bay housing.
- Lockable Container Doors with option for Roller Door.
- Supplied with Interstitial Emergency Relief Vent that will relieve the gap between the two tanks in the event of a fire.
- DN80 Fill Point c/w Camlock Male Fitting / Dust Cap / Fire Safe Full Bore Ball Valve / Wafer Style Non Return Valve.
- Engineered Low Point and dedicated Suction Spear assembly for Water Draw Off
- DN80 Suction Outlet c/w Anti Syphon Valve and Two Piece Full Bore Fire Safe Ball Valve.
- DN80 Mechanical Overfill Valve + 12V Battery Operated Overfill Alarm.
- 2 x 600mm manways with integrated tank access ladder assembly.
- Fold out AS1657 designed and approved access ladder.
- Removable plate to allow the linking of multiple tanks in tank farm applications.
- Full under tank visibility allows for regular visual inspection of the tank base and prevents the base rusting by providing unrestricted air flow under the tank.
- Paint Colour RAL9003 Signal White. Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process. Primer Hempadur 1530. 2nd Coat Hempadur Hi-Build 4520. Final Coat Hemptane Enamel 55100. Finished dry film thickness no less than 180 um.
- Supplied with all required statutory safety decals for your region of operation.



CONTAINERISED SELF BUNDED TANK RANGE



PRODUCT RANGE

	CON-12	CON-18	CON-30	CON-38	CON-69	CON-75	CON-80	CON-90	CON-110
CAPACITY	12,000L	18,000L	30,000L	38,000L	69,000L	75,000L	80,000L	90,000L	1,10,000L
SAFE FILL LEVEL	10,100L	16,250L	27,000L	33,500L	65,000L	71,500L	76,000L	85,000L	1,06,500L
LENGTH (MM)	3,000	3,000	6,058	6,058	12,192	12,192	14,630	14,630	14,630
WIDTH (MM)	2,438	2,438	2,438	2,438	2,438	2,438	2,438	2,438	3,200
HEIGHT (MM)	2,896	2,896	2,896	2,896	2,896	2,896	2,896	2,896	3,200
WEIGHT (KG)	4,950	4,950	7,600	7,700	14,500	14,500	15,925	17,400	21,100
CONTAINER FOOTPRINT	10FT HIGH	10FT HIGH	20FT HIGH	20FT HIGH	40FT HIGH	40FT HIGH	48FT HIGH	48FT HIGH	BREAK BULK
INTEGRATED PUMP BAY	YES	NO	YES	NO	YES	NO	YES	NO	YES



Bunded Lockable Pump Bay



A Look On Top



CSC Plated as Standard Container

